

Visokonaponske Baterije HV2600 2600 W



Jednostavna instalacija



Nizak napon



Visoka efikasnost



Razvijen sistem



90% Dubina pražnjenja

Specifikacija

Model	HS5.2	HS7.8	HS10.4	HS13	HS15.6	HS18.2	HS20.8
Tip baterije	LiFePO4 Prismatic Cell						
Modul baterije	1*BMS BOX HV 2*HV2600	1*BMS BOX HV 3*HV2600	1*BMS BOX HV 4*HV2600	1*BMS BOX HV 5*HV2600	1*BMS BOX HV 6*HV2600	1*BMS BOX HV 7*HV2600	1*BMS BOX HV 8*HV2600
Nominalni kapacitet (Wh)	5120	7680	10240	12800	15360	17920	20480
Nominalna snaga (V)	102.4	153.6	204.8	256	307.2	358.4	409.6
Radna snaga (V)	80 - 116.8	120 - 175.2	160 - 233.6	200 - 292	240 - 350.4	280 - 408.8	320 - 467.2
Preporučena struja pražnjenja (A)	25						
Maksimalna struja punjenja / pražnjenja (A)	50						
Vršna struja pražnjenja (A)	65A @30sec						
Efikasnost baterije pri povratnom putu	>95%						
Dubina pražnjenja	90%						
Ciklus života	≥6000*						
Komunikacija	CAN, RS485						
Ekran	HV 2600: LED*2, BMS BOX HV: LED*7						
Prilagodljivost	Maks. 8 modula u seriji						
Lokacija instalacije	U zatvorenom (stalak)						
Radna temperatura (°C)	-10 - 50						
Storage Temperature [°C]	-20 - 50						
Metoda hlađenja	Prirodna konvekcija						
Vlažnost	5% - 85% (bez kondenzacije)						
Domet (m)	Max. 2,000						
Dimenzije (mm) [BMS BOX HV]	420*116*480						
Težina (kg) [BMS BOX HV]	4.5						
Dimenzije (mm) [HV2600]	420*116*480						
Težina (kg) [HV2600]	29.7±1						
Sigurnost	IEC 62619						
EMC	EN IEC 61000-6-1/2/3/4						
Transport	UN38.3						
Ulazna zaštita	IP21						