

Niskonaponske Baterije LV2600 2600 W



Jednostavna instalacija



Nizak napon



Visoka efikasnost



Razvijen sistem



90% Dubina pražnjenja



Specifikacija

Tip baterije	LiFePO4 Prismatic Cell
Nominalni kapacitet (Wh)	2560
Nominalna snaga (V)	51.2
Radna snaga (V)	43.2 - 57.6
Preporučena struja pražnjenja (A)	25
Maksimalna struja punjenja / pražnjenja (A)	50
Vršna struja pražnjenja (A)	100A @15sec
Efikasnost baterije pri povratnom putu	>95%
Dubina pražnjenja	90%
Ciklus života	≥6000**
Komunikacija	CAN, RS485
Ekran	LED*5
Prilagodljivost	Maks. 12 modula paralelno
Lokacija instalacije	U zatvorenom (stalak)
Radna temperatura (°C)	-20 - 55
Storage Temperature [°C]	-20 - 55
Metoda hlađenja	Prirodna konvekcija
Vlažnost	5% - 85% (bez kondenzacije)
Domet (m)	Max. 2,000
Dimenzije (mm)	440 * 440 * 116
Težina (kg)	28.9
Sigurnost	IEC62619
EMC	IEC61000-6-1/3
Transport	UN38.3
Ulazna zaštita	IP21

