


Fox Hybrid/Ac Inverter

Single Phase

H1 & AC1
3-6kW



Easy Installation

Flexible configuration, plug and play set-up, built-in fuse protection.



High Voltage

Connects to high-voltage batteries for maximum round-trip efficiency.



IP65 Rated

Engineered to last with maximum flexibility. Suitable for outdoor installation.



Remote Monitoring

Monitor your system remotely via smartphone app or web portal.

TECHNICAL SPECIFICATIONS

Model	H1-3.0-E AC1-3.0-E	H1-3.7-E AC1-3.7-E	H1-4.6-E AC1-4.6-E	H1-5.0-E AC1-5.0-E	H1-6.0-E AC1-6.0-E
INPUT PV (Only for hybrid)					
Max. Input Power [W]	3900	4680	5980	6500	7800
Max. Input Voltage [V]			600		
Start-up Input Voltage [V]			75		
Rated Input Voltage [V]			360		
MPPT Operating Voltage Range [V]			80-550		
Max. Input Current [A]			13.5/13.5		
Max. Short-circuit Current [A]			15/15		
No. of Independent MPP Trackers	2	2	2	2	2
No. of Strings per MPP Tracker	1	1	1	1	1
BATTERY CONNECTION					
Battery Type	Lithium Battery (LFP)				
Battery Voltage [V]	85-450				
Max. Charge/Discharge Current [A]	40				
Communication Interface	CAN(Communicate With Inverter), RS485 (Upgrade BMS)				
AC INPUT AND OUTPUT (GRID)					
Max. AC Input Power [VA]	7000	7680	9600	10000	12000
Max. AC Input Current (per phase) [A]	31.8	34.9	43.6	45.5	54.5
Rated Output Power [W]	3000	3680	4600	5000	6000
Max. Output Apparent Power [VA]	3300	4048	5060	5500	6600
Rated Output Current (per phase) [A]	13.0	16.0	20.0	21.7	26.1
Max. Output Current [A]	14.3	17.6	22.0	23.9	28.7
Rated Grid Voltage [V]	220/230/240				
Rated Grid Frequency [Hz]	50/60				
Power Factor	1 (Adjustable from 0.8 leading to 0.8 lagging)				
THDi	<3% @rated power				
EPS OUTPUT (WITH BATTERY)					
Max. Output Apparent Power [VA]	5000	5000	6000	6000	6000
Peak Output Apparent Power (60s) [VA]	6000	6000	7200	7200	7200
Max. Current (per phase) [A]	21.7	21.7	26.1	26.1	26.1
Rated Output Voltage [V]	220/230/240				
Rated Output Frequency [Hz]	50/60				
Power Factor	1 (Adjustable from 0.8 leading to 0.8 lagging)				
THDv (linear Load)	<2% @rated power				
Switch time [ms]	<20				
EFFICIENCY					
Euro Efficiency	97.00%	97.00%	97.00%	97.00%	97.00%
Max. Efficiency	97.80%	97.80%	97.80%	97.80%	97.80%
Max. Battery Charge Efficiency (PV to BAT) (@full load)	98.50%	98.50%	98.50%	98.50%	98.50%
Max. Battery Discharge Efficiency (BAT to AC) (@full load)	97.00%	97.00%	97.00%	97.00%	97.00%
PROTECTION					
Insulation Monitoring	YES				
Residual Current Monitoring	YES				
DC Reverse Polarity Protection	YES				
Anti-islanding Protection	YES				
AC Short-circuit Protection	YES				
AC Overcurrent/Overvoltage Protection	YES				
DC Switch	YES				
SPD	DC: Type II, /AC: Type III				
GENERAL DATA					
Dimensions (WxHxD) [mm]	430*410*178				
Weight [kg]	23				
Installation	Wall-Mounted				
Topology	Transformerless				
Cooling Method	Neutral				
Noise Emission [dB]	35				
Max. Operating Altitude [m]	2000				
Operating Temperature Range [°C]	-25 to 60				
Humidity (No Condensation)	0% to 100%				
Protection Degree	IP65				
Standby consumption[W]	<10				
Monitoring Module	WiFi, LAN, 4G, GPRS (Optional)				
Communication	2*RS485, DRM, Ripple Control, USB				
Display	LCD, App, Website				
STANDARD COMPLIANCE (MORE AVAILABLE UPON REQUEST)					
Safety	EN 62109-1, EN 62109-2				
EMC	EN 61000-6-2, EN 61000-6-3				
Grid Regulation	EN50549-1, C10 / 11, VDE-AR-N 4105, G98, G99, CEI 0-21, NRS 097-2-1, AS / NZS 4777.2				