

Low Voltage Battery LV2600 2.56 kWh



Easy Installation



Low Voltage



High Efficiency



Expandable System



90% Depth of Discharge

SPECIFICATIONS

Battery Type	LiFePO4 Prismatic Cell
Nominal Capacity [Wh]	2560
Nominal Voltage [V]	51.2
Operating Voltage [V]	43.2 - 57.6
Recommend Discharge Current [A]	25
Max.Charge/Discharge Current [A]	50
Peak Discharge Current [A]	100A @15sec
Battery Pack Round-Trip Efficiency	>95%
Depth of discharge	90%
Cycle Life	>6000 ^{*1}
Communication	CAN, RS485
Display	LED*5
Scalability	Max. 12 Modules in Parallel
Installation Location	Indoor (Stand)
Operating Temperature [°C]	-20 - 55
Storage Temperature [°C]	-20 - 55
Cooling Method	Natural Convection
Humidity	5% to 85% (No Condensing)
Altitude [m]	Max. 2,000
Dimensions (W*H*D) [mm]	440 * 440 * 116
Weight [kg]	28.9
Safety	IEC62619
EMC	IEC61000-6-1/3
Transportation	UN38.3
Ingress Protection	IP21

*1 25 C, @90% DOD, 0.5C charging/discharging